



丹佛斯美優樂全密閉壓縮機



型號 Model		蒸發溫度 EVAPORATING TEMPERATURE	冷凍能力CAPACITY R404A						
			-45°C	-40°C -40°F	-34.4°C -30°F	-28.8°C -20°F	-23.3°C -10°F	-17.8°C 0°F	-12.2°C 10°F
NTZ048 (同LTZ22)	冷凍能力 BTU	37.8°C/100°F	1,347	2,478	4,072	6,070	8,532	11,517	15,091
		48.9°C/120°F	860	1,412	2,653	4,214	6,153	8,533	11,420
		54.4°C/130°F		935	1,990	3,323	4,991	7,057	9,589
	耗電流 A	37.8°C/100°F	2.85	3.47	4.05	4.56	5.04	5.53	6.07
		48.9°C/120°F	2.43	2.95	3.81	4.57	5.28	5.97	6.69
		54.4°C/130°F		2.51	3.53	4.45	5.31	6.13	6.97
NTZ068 (同LTZ28)	冷凍能力 BTU	37.8°C/100°F	2,957	4,627	6,956	9,855	13,414	17,725	22,885
		48.9°C/120°F	2,289	3,106	4,926	7,192	9,990	13,416	17,570
		54.4°C/130°F		2,453	4,032	5,995	8,431	11,432	15,101
	耗電流 A	37.8°C/100°F	4.33	5.89	6.51	7.11	7.73	8.40	9.17
		48.9°C/120°F		5.54	6.47	7.34	8.21	9.12	10.1
		54.4°C/130°F		5.18	6.30	7.35	8.39	9.46	10.6
NTZ108 (同LTZ44)	冷凍能力 BTU	37.8°C/100°F	3,733	5,794	9,437	14,123	20,027	27,335	36,234
		48.9°C/120°F		3,595	6,478	10,152	14,791	20,577	27,707
		54.4°C/130°F			4,955	8,101	12,086	17,091	23,314
	耗電流 A	37.8°C/100°F	6.73	7.42	8.44	9.54	10.7	12.0	13.5
		48.9°C/120°F		7.14	8.27	9.56	11.0	12.7	14.6
		54.4°C/130°F			8.03	9.42	11.0	12.9	15.0
NTZ136 (同LTZ50)	冷凍能力 BTU	37.8°C/100°F	5,351	7,814	12,314	17,932	24,839	33,210	43,226
		48.9°C/120°F		4,716	8,323	12,852	18,475	25,374	33,740
		54.4°C/130°F			6,414	10,352	15,285	21,397	28,888
	耗電流 A	37.8°C/100°F	8.89	9.84	11.3	13.0	14.7	16.4	18.1
		48.9°C/120°F		9.17	11.0	13.0	15.2	17.4	19.7
		54.4°C/130°F			10.6	12.8	15.2	17.7	20.4
NTZ215 (同LTZ88)	冷凍能力 BTU	37.8°C/100°F	8,037	12,959	19,810	28,333	38,782	51,420	66,516
		48.9°C/120°F	4,860	7,354	12,935	19,930	28,594	39,202	52,043
		54.4°C/130°F		4,650	9,465	15,563	23,200	32,655	44,229
	耗電流 A	37.8°C/100°F	12.07	14.4	16.9	19.2	21.7	24.4	27.4
		48.9°C/120°F		12.9	16.5	19.8	23.0	16.1	29.4
		54.4°C/130°F		11.4	15.7	19.7	23.3	26.9	30.4
NTZ271 (同LTZ100)	冷凍能力 BTU	37.8°C/100°F	12,201	18,536	27,481	38,705	52,559	69,409	89,629
		48.9°C/120°F	9,054	12,230	19,389	28,389	39,581	53,341	70,063
		54.4°C/130°F		9,145	15,308	23,095	32,854	44,963	59,828
	耗電流 A	37.8°C/100°F	15.33	17.4	20.1	23.1	26.3	29.4	32.4
		48.9°C/120°F		17.5	20.5	24.0	27.8	31.7	35.7
		54.4°C/130°F		17.2	20.4	24.2	28.3	32.7	37.2

制冷量和輸入功率數據±5%

額定工況

60HZ 過熱度 5K 過冷度 3K 220V